

CoffeePRO-10

System Part: Replacement Cartridge:
#60-0600 CP Filter #102-160

- SPECIFICATIONS:**
- Rated Capacity: 15,000 Gal. / 56,780 L.
 - Flow Rate: 5 gpm
 - Min/Max Pressure: 40–125 psi.
 - Min/Max Temperature: 40°–100° F
 - Inlet/Outlet Size: 1/2 Inch Barbed Fitting
 - Shipping Weight: 17 lbs.
 - Dimensions (W/D/H): 17/9/18”



Rated capacity is based on extensive field testing in very challenging water conditions. This testing is performed by Selecto Scientific and its assignees.

COFFEE, TEA, ESPRESSO APPLICATION

FOR: Scale Inhibition, Scale Reduction, Chlorine, and Chlormaine Reduction

VOLUME: Low to High

SPECIFIED TO:

- Inhibit scale build up
- Reduce pitting of heating elements in Coffee/Tea Brewers.

SPECIFIED FOR:

- Coffee and Tea Brewers

TECHNOLOGY:

- Siliphos Scale Inhibitor
- Carbon Fiber Block

APPLICATIONS:

- Coffee Brewers
- Tea Brewers

SIZING:

Up to 5 GPM flow rate



• ANSI/NSF Component System tested and certified by NSF International. Please contact www.NSF.org for specifications.



SELECTO SCIENTIFIC
INCORPORATED

3980 Lakefield Court, Suwanee, GA 30024 USA • 800-635-4017 • 678-475-0799
www.selectoinc.com • ©2004 Selecto Scientific, Inc. All Rights Reserved.