

Espresso 12000

System Part: Replacement Cartridge:
#67-1620 #101-620

SPECIFICATIONS:

- Rated Capacity (Gallons): 12,000
- Flow Rate: 2 gpm
- Min/Max Pressure: 40–125 psi.
- Min/Max Temperature: 40°–100° F
- Inlet/Outlet Size: 1/2 Inch Barbed Fitting
- Shipping Weight: 32 lbs.
- Dimensions (W/D/H): 17/9/28”



COFFEE, TEA, ESPRESSO APPLICATION

FOR: Hardness/Scale Effects, Off Tastes and Odors, Chlorine, Chloramine, Alkalinity Reduction

VOLUME:
High

SPECIFIED TO:

- Provide chlorine free water for coffee, tea and espresso
- Reduce lime scale build up
- Reduce pitting of stainless steel steam generators, tanks and fans
- Reduce equipment maintenance
- Enhance the flavor of coffee, tea and espresso

SPECIFIED FOR:

- Heating elements with or without flush cycles

TECHNOLOGY:

- CeramicMATRIX
- NanoCRYSTAL
- FLOW Dynamics
- Radial Integrated Carbon

INGREDIENT WATER

CONTAMINANT REDUCTION OF:

Chlorine, Chloramine, Bad Taste and Odors, Total Organic Carbon, Volatile Organic Compounds, Tannins, Turbidity, Cryptosporidium Cyst, Giardia Cyst and Trihalomethanes

APPLICATIONS:

Coffee, Tea, Espresso and Cappuccino Machines



• ANSI/NSF Component



SELECTO SCIENTIFIC
INCORPORATED

3980 Lakefield Court, Suwanee, GA 30024 USA • 800-635-4017 • 678-475-0799
www.selectoinc.com • ©2006 Selecto Scientific, Inc. All Rights Reserved.