

# Espresso 7500

System Part: #67-1600  
Replacement Cartridge: #101-600

## SPECIFICATIONS:

- Rated Capacity (Gallons): 7,500
- Flow Rate: 1 gpm
- Min/Max Pressure: 40–125 psi.
- Min/Max Temperature: 40°–100° F
- Inlet/Outlet Size: 1/2 Inch Barbed Fitting
- Wet Weight: 21 lbs.
- Shipping Weight: 17 lbs.
- Dimensions (W/D/H): 17/9/18”



## COFFEE, TEA, ESPRESSO APPLICATION

**FOR:** Scale Inhibition, Chlorine, Chloramine, Sediment, THM'S Bad Taste & Odor, Organics & Tannins Reduction

**VOLUME:** Low - Medium

## SPECIFIED TO:

- Provide chlorine free water for coffee, tea and espresso
- Reduce lime scale build up
- Reduce pitting of stainless steel steam generator, tanks and fans
- Reduce equipment maintenance
- Enhance the flavor of coffee, tea and espresso

## SPECIFIED FOR:

- Heating elements with or without flush cycles

## TECHNOLOGY:

- CeramicMATRIX
- NanoCRYSTAL
- FLOW Dynamics
- Radial Integrated Carbon

## INGREDIENT WATER CONTAMINANT REDUCTION OF:

Chlorine, Chloramine, Bad Taste and Odors, Total Organic Carbon, Volatile Organic Compounds, Tannins, Turbidity, Cryptosporidium Cyst, Giardia Cyst and Trihalomethanes

## APPLICATIONS:

Coffee, Tea, Espresso and Cappuccino Machines



• ANSI/NSF Component

Rated capacity is based on extensive field testing in very challenging water conditions. This testing is performed by Selecto Scientific and its assignees.



**SELECTO SCIENTIFIC**  
INCORPORATED

3980 Lakefield Court, Suwanee, GA 30024 USA • 800-635-4017 • 678-475-0799  
www.selectoinc.com • ©2006 Selecto Scientific, Inc. All Rights Reserved.