

# IC 600

System Part: #60-0600IC  
Replacement Cartridge: #101-390

- SPECIFICATIONS:**
- Rated Capacity:
    - \*Chlorine: 50,000 gallons @ 5 gpm
    - Chloramine: 15,000 gallons @ 2.5 gpm
  - Flow Rate: 5 gpm
  - Min/Max Pressure: 40–125 psi.
  - Min/Max Temperature: 40°–100° F
  - Inlet/Outlet Size: 1/2 Inch Barbed Fitting
  - Shipping Weight: 17 lbs.
  - Dimensions (W/D/H): 17/9/18”



## JUICE APPLICATION

**FOR:** Chlorine, Chloramine, Sediment, THMs, Organics, Tannins, Bad Taste and Odor Reduction

**VOLUME:**  
Low – Medium

### SPECIFIED TO:

- Improve the taste of juices
- Provide safe, clean ingredient water for juice machines
- Reduce equipment maintenance
- Increase juice sales

### SPECIFIED FOR:

- Fountain and multi-use application such as juice, ice, coffee and tea

### TECHNOLOGY:

- Super High Porosity Carbon with Micro Structure

### INGREDIENT WATER

**CONTAMINANT REDUCTION OF:** Chlorine, Chloramine, Bad Tastes and Odors, Total Organic Carbon, Tannins, Turbidity, and Trihalomethanes

### APPLICATIONS:

Juice Machines

Rated capacity is based on extensive field testing in very challenging water conditions. This testing is performed by Selecto Scientific and its assignees.



**SELECTO SCIENTIFIC**  
INCORPORATED

3980 Lakefield Court, Suwanee, GA 30024 USA • 800-635-4017 • 678-475-0799  
www.selectoinc.com • ©2006 Selecto Scientific, Inc. All Rights Reserved.



NSF Standard 42 system tested and certified by NSF International. Please contact [www.NSF.org](http://www.NSF.org) for specifications.